

OP-5S1508A,OP-5S1508B,OP-5S1515B,OP-5S1515C



OP-5S1508A
OP-5S1508B **F**
OP-5S1515B
OP-5S1515C
 Air shut off
 Rear exhaust
 自動斷氣
 後排氣

Specifications:

OP-5S1508 / OP-5S1515: Push start, Air shut off, Rear exhaust

- With push-start device, all parts stop working automatically while reaching the torque.
- Rear exhaust, low noise, low air consumption, and save energy.

Application:

- Apply to release or fasten heavy-precise screws.
- Apply especially to industry assembly lines such as computer, instrument, and electric

MODEL	Screw Size	MAX.	Free	Air		Overall		Air	Net		Sound
	Capacity	Torque	Speed	Consumption	Consumption	Length	Inlet	Weight	Weight	Level	
	mm	Nm	rpm	l/min	cfm	mm	inch	P.T	kg	lb	dB(A)
OP-5S1508A	5	2.8~4.0	800	198	7	285	11.22	4-Jan	0.95	2.09	75
OP-5S1508B	4	1.9~2.8	800	198	7	285	11.22	4-Jan	0.95	2.09	75
OP-5S1515B	4	1.4~2.6	1400	198	7	285	11.22	4-Jan	0.95	2.09	75
OP-5S1515C	3.5	0.9~1.6	1400	198	7	285	11.22	4-Jan	0.95	2.09	75