

OP-914DA3, DAZ3, DA6, DAZ6



Specifications:

OP-914DA3: Side exhaust

• Outside trigger: OP-914DA3 with driver anvil length 1/2", OP-914DA6 with driver anvil length 6"

• Inside trigger: OP-914DAZ3 with driver anvil length 1/2", OP-914DAZ6 with driver anvil length 6"

MODEL	Bolt Size	Working Torque		MAX. Torque		Free Speed	Air Consumption		Overall Length		Air Inlet	Net Weight		Sound Level
	Capacity	Nm	ft-lb	Nm	ft-lb		l/min	cfm	mm	inch		P.T	kg	
OP-914DA3	M27~M30	1355	1000	2700~3000	1990~2210	2800	452	16	418	16.46	8-Mar	11.5	25.44	100
OP-914DAZ3	M27~M30	1355	1000	2700~3000	1990~2210	2800	452	16	418	16.46	8-Mar	11.5	25.44	100
OP-914DA6	M27~M30	1355	1000	2700~3000	1990~2210	2800	452	16	543	21.38	8-Mar	13.3	29.23	100
OP-914DAZ6	M27~M30	1355	1000	2700~3000	1990~2210	2800	452	16	543	21.38	8-Mar	13.3	29.23	100