

OP-913D2, D6, D8, DZ2, DZ6, DZ8



Specifications:

OP-913D2: Side exhaust, Light type

• Outside trigger: OP-913D2 with driver anvil length 1/2", OP-913D6 with driver anvil length 6-1/2", OP-913D8 with driver anvil length 8-1/2"

• Inside trigger: OP-913DZ2 with driver anvil length 1/2", OP-913DZ6 with driver anvil length 6-1/2", OP-913DZ8 with driver anvil length 8-1/2"

MODEL	Bolt Size Capacity		Working Torque		MAX. Torque		Free Speed rpm	Air Consumption		Overall Length		Air Inlet P.T	Net Weight		Sound Level dB(A)
	mm		Nm	ft-lb	Nm	ft-lb		l/min	cfm	mm	inch		kg	lb	
OP-913D2	M24		1000	738	1800~2000	1320~1470	4000	424	15	350	13.78	8-Mar	6.6	14.55	102
OP-913D6	M24		1000	738	1800~2000	1320~1470	4000	424	15	500	19.69	8-Mar	7.4	16.31	102
OP-913D8	M24		1000	738	1800~2000	1320~1470	4000	424	15	550	21.65	8-Mar	7.8	17.2	102
OP-913DZ2	M24		1000	738	1800~2000	1320~1470	4000	424	15	350	13.78	8-Mar	6.6	14.55	102
OP-913DZ6	M24		1000	738	1800~2000	1320~1470	4000	424	15	500	19.69	8-Mar	7.4	16.31	102
OP-913DZ8	M24		1000	738	1800~2000	1320~1470	4000	424	15	550	21.65	8-Mar	7.8	17.2	102