

OP-914D2, D6, D8, DZ2, DZ6, DZ8



Specifications:

OP-914D2: Side exhaust

• Outside trigger: OP-914D2 with driver anvil length 1/2", OP-914D6 with driver anvil length 6-1/2", OP-914D8 with driver anvil length 8-1/2"

• Inside trigger: OP-914DZ2 with driver anvil length 1/2", OP-914DZ6 with driver anvil length 6-1/2", OP-914DZ8 with driver anvil length 8-1/2"

MODEL	Bolt Size	Working Torque		MAX. Torque		Free Speed	Air Consumption		Overall Length		Air Inlet	Net Weight		Sound Level
	Capacity	Nm	ft-lb	Nm	ft-lb		l/min	cfm	mm	inch		P.T	kg	
OP-914D2	M27~M30	1355	1000	2500~2900	1840~2130	2800	452	16	393	21.7	8-Mar	10.3	22.7	100
OP-914D6	M27~M30	1355	1000	2500~2800	1840~2060	2800	452	16	543	21.4	8-Mar	12.3	27.1	100
OP-914D8	M27~M30	1355	1000	2500~2800	1840~2060	2800	452	16	594	23.4	8-Mar	13.3	29.3	100
OP-914DZ2	M27~M30	1355	1000	2500~2900	1840~2130	2800	452	16	393	15.5	8-Mar	10.3	22.7	100
OP-914DZ6	M27~M30	1355	1000	2500~2800	1840~2060	2800	452	16	543	21.4	8-Mar	12.3	27.1	100
OP-914DZ8	M27~M30	1355	1000	2500~2800	1840~2060	2800	452	16	594	23.4	8-Mar	13.3	29.3	100