


OP-08AK



OP-08AK
Rear exhaust
後排氣



扭力筒夾規格表
Chuck standards and size list

FOR TAP	JIS 日本標準規格				ISO 國際標準規格				DIN 371 德國標準規格				DIN 376 德國標準規格			
	Thread	∅ d	□	Order Code 訂貨號	∅ d	□	Order Code 訂貨號	∅ d	□	Order Code 訂貨號	∅ d	□	Order Code 訂貨號	∅ d	□	Order Code 訂貨號
M2	3	2.5	TCJISM2													
M3	4	3.2	TCJISM3	3.15	2.5	TCISOM3	3.5	2.7	TCDIN371M3	2.2	-					TCDIN376M3
M4	5	4	TCJISM4	4	3.15	TCISOM4	4.5	3.4	TCDIN371M4	2.8	2.1					TCDIN376M4
M5	5.5	4.5	TCJISM5	5	4	TCISOM5	6	4.9	TCDIN371M5	3.5	2.7					TCDIN376M5
M6	6	4.5	TCJISM6	6.3	5	TCISOM6	6	4.9	TCDIN371M6	4.5	3.4					TCDIN376M6
M8	6.2	5	TCJISM8	8	6.3	TCISOM8	8	6.2	TCDIN371M8	6	4.9					TCDIN376M8
M10	7	5.5	TCJISM10	10	8	TCISOM10	10	8	TCDIN371M10	7	5.5					TCDIN376M10
M12	8.5	6.5	TCJISM12	9	7.1	TCISOM12				9	7					TCDIN376M12

FOR TAP	ANSI 美國標準規格			
Thread	∅ d	□	Order Code 訂貨號	
1/2"	9.322	6.985	TCANSI W 1/2	

Air Tapping Order Code Reference

Model 型號	OP-11AK	OP-08AK	OP-12AK	備註： 筒夾標準出貨規格為JIS，如需其他規格筒夾，請參考扭力筒夾規格表，並於訂單上註明筒夾規格。
Size 規格	Order Code 訂貨號			
M2		OP-08AK-2		NOTICE: When different sizes or standard chucks are needed, please refer to the chuck standards and size list and note on the purchase order, otherwise, the chuck will be JIS.
M3	OP-11AK-3	OP-08AK-3	OP-12AK-3	
M4	OP-11AK-4	OP-08AK-4	OP-12AK-4	
M5	OP-11AK-5	OP-08AK-5	OP-12AK-5	
M6	OP-11AK-6	OP-08AK-6	OP-12AK-6	
M8	OP-11AK-8	OP-08AK-8	OP-12AK-8	
M10	OP-11AK-10		OP-12AK-10	
M12	OP-11AK-12		OP-12AK-12	

MODEL	Tapping Capacity (mm)			Free Speed rpm	Air Consumption		Overall Length		Air Inlet P.T	Net Weight		Sound Level dB(A)
	Aluminum	Copper	Iron		l/min	cfm	mm	inch		kg	lb	
OP-08AK	2~8	2~8	2~4	350	226	8	290	11.42	4-Jan	1.68	3.7	87